RECYCLED ROLLED RUBBER · DUAL LAYER

STRENGTH SELECT

Versatile & Heavy Usage

Select is our value-engineered recycled rubber — a proven commercial workhorse.

- Popular colors
- Force Reduction, Sound and Vibration
- Color Economy, Zone-able Budget



SPECIFICATIONS

Thicknesses	16mm (10+6), 18mm (10+8)
Width	4ft
Length	25ft & 50ft
Color %	0, 10, 20, 95
Colors	16mm (4), 18mm (13)
Warranty	3 Years

APPLICATIONS

- Olympic Lifting
- Heavy Free Weights
- Dropped-Load Zones

CONSTRUCTION

- Color top layer
- Black base layer

508-816-2604 sales@spsurfacing.com

STRENGTH SELECT DUAL LAYER COLORS / SPECS

16MM




Black
0%



Blue
10%



Gray
10%



Blue & Gray
10%

18MM




Black
0%




Blue
10%, 20%



Gray
10%, 20%



Blue & Gray
10%, 20%



Bright Red
10%




Brick Red
10%



Green
10%




Cocoa
10%




Purple
10%




Orange
10%



Red & Gray
20%




Granite
95%




Sandstone
95%


CUSTOM COLOR CONCENTRATION OPTIONS




20%




30%




40%



50%



60%



70%

SPECS

SPECIFICATION	TEST METHOD	TYPICAL VALUE
Tensile Strength	ASTM D412	266 PSI
Density	ASTM D3676	65 lb / cubic foot
Tear Resistance	ASTM D413	Average Elongation at Break 1.55
Hardness	ASTM D2240	Shore A 65 +/- 5
Compression Set	ASTM D395	-4.90%
VOC Emissions	ASTM DS116	0.5 mg/m² or less
Flammability	ASTM D2859	PASS
Resistance to Chemicals	F-925-02	Resistance to most acids and chlorine
Coefficient of Friction	ASTM D1894/5	>0.8

SPORT PRO
SURFACING

CONTACT US

508-816-2604 sales@spsurfacing.com