RECYCLED ROLLED RUBBER

STRENGTH SELECT

Versatile & Reliable

Select is our value-engineered recycled rubber — a proven commercial workhorse.

- Popular colors
- Quick Ship



SPECIFICATIONS

Thicknesses	9mm, 12mm
Width	4ft
Length	25ft & 50ft
Color %	0, 10
Colors	9mm (4), 12mm (4)
Warranty	3 Years

APPLICATIONS

- Free-weight Areas
- Functional Training
- Performance Spaces

CONSTRUCTION


Single layer · 9mm or 12mm


508-816-2604 sales@spsurfacing.com


STRENGTH SELECT COLORS / SPECS

9MM


Black


Blue
10%



Gray
10%



Blue & Gray
10%

12MM



Black



Blue
10%



Gray
10%



Blue & Gray
10%


CUSTOM COLOR CONCENTRATION OPTIONS



20%


30%


40%


50%


60%


70%

SPECS

SPECIFICATION	TEST METHOD	TYPICAL VALUE
Tensile Strength	ASTM D412	266 PSI
Density	ASTM D3676	65 lb / cubic foot
Tear Resistance	ASTM D413	Average Elongation at Break 1.55
Hardness	ASTM D2240	Shore A 65 +/- 5
Compression Set	ASTM D395	-4.90%
VOC Emissions	ASTM DS116	0.5 mg/m² or less
Flammability	ASTM D2859	PASS
Resistance to Chemicals	F-925-02	Resistance to most acids and chlorine
Coefficient of Friction	ASTM D1894/5	>0.8

SPORT PRO SURFACING

CONTACT US

508-816-2604 sales@spsurfacing.com