RECYCLED INTERLOCKING TILES

STUDIO SELECT

Versatile & Reliable

STUDIO SELECT LOCK TILES

Select is our value-engineered recycled rubber — a proven commercial workhorse.

- Popular colors
- Two Size Options



SPECIFICATIONS

Thicknesses	6mm, 8mm
Sizes	24" x 24" or 47" x 47"
Color %	0, 10, 20, 95
Colors	6mm (4), 8mm (13)
Warranty	3 Years

APPLICATIONS

- Group Fitness
- Cardio Decks
- Multi-Purpose Rooms
- General Training

CONSTRUCTION



Single layer interlocking tile · 6mm or 8mm

508-816-2604 sales@spsurfacing.com


STUDIO SELECT TILES COLORS / SPECS

6MM


Black
0%


Blue
10%


Gray
10%



Blue & Gray
10%


8MM


Black
0%


Blue
10%, 20%


Gray
10%, 20%



Blue & Gray
10%, 20%


Bright Red
10%



Brick Red
10%



Green
10%



Cocoa
10%


Purple
10%



Orange
10%



Red & Gray
20%



Granite
95%



Sandstone
95%


CUSTOM COLOR CONCENTRATION OPTIONS



20%


30%


40%


50%


60%


70%

SPECS

SPECIFICATION	TEST METHOD	TYPICAL VALUE
Tensile Strength	ASTM D412	266 PSI
Density	ASTM D3676	65 lb / cubic foot
Tear Resistance	ASTM D413	Average Elongation at Break 1.55
Hardness	ASTM D2240	Shore A 65 +/- 5
Compression Set	ASTM D395	-4.90%
VOC Emissions	ASTM DS116	0.5 mg/m² or less
Flammability	ASTM D2859	PASS
Resistance to Chemicals	F-925-02	Resistance to most acids and chlorine
Coefficient of Friction	ASTM D1894/5	>0.8

SPORT PRO
SURFACING

CONTACT US

508-816-2604 sales@spsurfacing.com