CARE GUIDE

ARIA

Applies to: Aria Performance Vinyl Plank

SPORT PRO SURFACING

01

INITIAL CONSTRUCTION CLEANING

1. Wait at least 24–48 hours after installation before the first cleaning.
2. Remove all loose debris, dust, and grit by sweeping and vacuuming.
3. Remove all traces of adhesive from the surface using a clean white cloth dampened with mineral spirits or denatured alcohol.
4. Damp mop with a microfiber mop, using a neutral-pH cleaner diluted at roughly 10 oz per gallon of cool water.

> **IMPORTANT**
> Do not flood the floor at any point in the cleaning process — doing so can risk a warranty exclusion.

02

ROUTINE MAINTENANCE

1. Use entryway/walk-off mats to reduce dirt, sand, and grit being tracked onto the floor.
2. Sweep, mop, or vacuum regularly to remove dust and loose dirt.
3. Spot-mop stubborn marks with the same neutral-pH cleaner, diluted at roughly 3 oz per gallon of cool water.
4. Damp mop the full floor periodically with the same 3 oz/gallon dilution, and allow to dry.

REFERENCE TABLE

STEP	DILUTION	COVERAGE	TOOLS
Initial Cleaning	10 oz cleaner per gallon of water	~2,000 sq ft/gal	Microfiber mop — do not flood floor
Routine Cleaning	3 oz cleaner per gallon of water	~6,000 sq ft/gal	Microfiber mop — do not flood floor

03

A FEW MORE NOTES

- Fit protective feet to all furniture and fixtures to prevent marking, scratching, or other damage.
- **Avoid rubber feet, rubber casters, or rubber-backed mats** — these can cause permanent staining on vinyl surfaces.
- Chair mats are recommended under any seating with casters; going without one is considered a form of misuse.
- Regular, light cleaning is more effective and more cost-efficient than occasional heavy cleaning.