PERFORMANCE SHEET VINYL

ENCORE

Group X Room · Natural Design

VINYL ENCORE YOGA WELLNESS

- Class 2 shock absorption
- Exceptional resistance to static loads (chairs, tables, bleachers,...): ≤0.10mm*
- Superior resistance to heavy rolling loads
- Resistance to stains and scratches: 0.70mm PU-reinforced wear layer
- Wood look with comfort



SPECIFICATIONS

Thickness	6.2 mm (0.244")
Wear layer	0.7 mm
Colors	26
Width	2M
Length	26M
Warranty	25 Years

APPLICATIONS

- Group Exercise Rooms
- Wellness Spaces
- Multi-Purpose Rooms
- Heated Yoga Rooms

CONSTRUCTION


- Vinyl
- Moisture Barrier
- Base Layer

508-816-2604 sales@spsurfacing.com


COLORS


Nordic Oak


Concrete Gray Beige


Khaki


Gray Maple


Gray


Black Maple


Light Maple



Beech


Golden Maple


Blue Maple


Tonic Blue


Night Blue


Silver Gray


Concrete Cool Gray


Black


Natural Oak



Classic Oak



Concrete Deep Blue


Sky Blue Maple


Sky Blue


Tonic Green


Tonic Yellow


Tonic Orange


Tonic Red


Red Maple


Green Maple

508-816-2604 sales@spsurfacing.com

SPECS

SPECIFICATION	TYPICAL VALUE
Certification & Classification	Multi-Use
Ball Rebound	Passed
Force Reduction	Class 2
Surface Finish Effect	Passed
Vertical Deformation	Passed
Below-Room Sound Insulation	21 db
Microbial Resistance	No Growth
Reaction to Fire	Class 1 (Radiant Panel)
Resistance to Impact	No Degradation
Rolling Load	0.5 mm (No Degradation)
Roll Width	2 m (6.56 ft)
Chemical Resistance	Excellent
Static Load Tolerance	175 psi
Thickness	6.2 mm (0.244")
Wear Layer Performance Grade	Type 1, Grade 1, Commercial
Wear Layer Structure	2.0 mm
Wear Layer Thickness	0.7 mm
Weight	4.76 kg/m² (0.96lb/sq. ft.)

CONTACT US

508-816-2604 sales@spsurfacing.com